

qblock

[[Description](#)] [[Usage](#)] [[Options](#)] [[Notes](#)] [[Examples](#)] [[See also](#)]

Description

qblock locks the available job slots on a Qube! Worker.

Usage

qblock [*options*] *hostname*...

where *hostname* is the name of the host to be locked. It can be followed by 0 or more *hostnames*.

Options

Switch	Description
--all	lock all hosts
--down	lock down hosts
--panic	lock panicked hosts
--active	lock active hosts
--cluster <i>string</i>	lock hosts in <i>string</i> cluster
--group <i>string</i>	lock hosts in <i>string</i> group
--resources <i>string</i>	lock hosts based upon requirements expression <i>string</i>
--purge	Immediately stop job processes running on Worker
--lock	Lock the Worker (default: on) (deprecated and implied)
--unlock	Unlock the Worker (deprecated : use qbunlock)
--range <i>string</i>	Range <i>string</i> of CPU slots to lock/unlock
--value	Specify custom lock
--file <i>string</i>	Use the lock in the specified <i>string</i> file
--help	Command help
--version	Command version

Notes

Examples

Locks host render01 CPU slots 0 and 1:

```
% qblock --range 0,1 --lock render01
```

Locks all host render01 CPUs:

```
% qblock render01
```

See also

